


MULTIFIT TYPE



BS STANDARD CONNECTIONS

M20882F


90° BSP O-RING FEMALE COMPACT ELBOW 60° CONE
 BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 90° BSP O型圈内螺纹紧凑型弯头 (60° 锥)
 BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 90° KOMPAKTBOGEN 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)
 FEMMINA GAS 90° CONO 60° O-RING TIPO COMPATTO
 BS5200 / ISO 12151-6 (DADO SPINATO)



| PART. REF. | HOSE BORE | | | THREAD | DIMENSIONS mm | | | | | |
|---------------|-----------|------|------|-----------|------------------|------|------|------|----|----------------|
| | DN | inch | Size | | T | B | A | C | E | H ₁ |
| M20882-04-04F | 6 | 1/4" | - 04 | 1/4" - 19 | 4,0 | 20,0 | 4,9 | 22,0 | 14 | 19 |
| M20882-06-06F | 10 | 3/8" | - 06 | 3/8" - 19 | 7,0 | 23,1 | 6,1 | 27,5 | 19 | 22 |
| M20882-08-08F | 12 | 1/2" | - 08 | 1/2" - 14 | 9,3 | 24,9 | 6,5 | 31,1 | 22 | 27 |
| M20882-10-10F | 16 | 5/8" | - 10 | 5/8" - 14 | 12,5 | 24,6 | 9,7 | 32,5 | 24 | 28 |
| M20882-12-12F | 19 | 3/4" | - 12 | 3/4" - 14 | 15,0 | 37,5 | 8,5 | 36,0 | 27 | 32 |
| M20882-16-16F | 25 | 1" | - 16 | 1" - 11 | 20,0 | 51,8 | 10,6 | 44,0 | 36 | 38 |

M10610

BSP MALE FLAT SEAT
 BSP 外螺纹平面底座
 AGR FLACH DICHTEND
 MASCHIO GAS CILINDRICO SEDE PIANA



| PART. REF. | HOSE BORE | | | THREAD | DIMENSIONS mm | | | | | |
|--------------|-----------|------|------|-----------|------------------|------|------|---|----------------|--|
| | DN | inch | Size | | T | B | A | C | H ₁ | |
| M10610-04-04 | 6 | 1/4" | - 04 | 1/4" - 19 | 6,0 | 25,5 | 11,0 | | 19 | |
| M10610-06-06 | 10 | 3/8" | - 06 | 3/8" - 19 | 9,5 | 28,1 | 12,0 | | 22 | |
| M10610-06-08 | 10 | 3/8" | - 06 | 1/2" - 14 | 13,0 | 30,6 | 14,0 | | 27 | |
| M10610-08-08 | 12 | 1/2" | - 08 | 1/2" - 14 | 13,0 | 31,1 | 14,0 | | 27 | |
| M10610-12-12 | 19 | 3/4" | - 12 | 3/4" - 14 | 18,0 | 35,5 | 16,0 | | 32 | |