


# MULTIFIT TYPE



## DIN STANDARD CONNECTIONS


### M21312

METRIC FEMALE MULTISEAL - DIN 20078/3868 (THRUST-WIRE NUT)  
 公制内螺纹组合密封 - DIN 20078/3868 (带止推金属丝螺母)  
 DKL UNIVERSALKONUS - DIN 20078/3868 (GESTIFTETE MUTTER)  
 FEMMINA METRICA CONO UNIVERSALE - DIN 20078/3868 (DADO SPINATO)



### M21313

METRIC FEMALE MULTISEAL - DIN 20078/3868 (SLIP-ON NUT)  
 公制内螺纹组合密封 - DIN 20078/3868 (带滑套螺母)  
 DKL UNIVERSALKONUS - DIN 20078/3868 (HINTERLEGTE MUTTER)  
 FEMMINA METRICA CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size			T	mm	B	A	C	H <sub>2</sub>
M21313-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	18,6	3,7			14
M21312-04-12	6	1/4"	- 04	M 12x1,5	6	4,0	19,5	4,0			17
M21313-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	19,5	3,8			17
M21313-04-16	6	1/4"	- 04	M 16x1,5	10	4,0	19,5	4,0			19
M21313-05-16	8	5/16"	- 05	M 16x1,5	10	5,5	19,5	4,0			19
M21313-05-18	8	5/16"	- 05	M 18x1,5	12	5,5	19,6	4,0			22
M21312-06-14	10	3/8"	- 06	M 14x1,5	8	4,0	19,5	3,9			17
M21312-06-16	10	3/8"	- 06	M 16x1,5	10	7,0	21,6	5,0			19
M21313-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	20,1	4,0			22
M21313-06-22	10	3/8"	- 06	M 22x1,5	15	7,0	21,1	5,2			27
M21312-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	23,0	5,9			22
M21313-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	21,5	5,2			27
M21313-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	22,1	5,5			32

# MULTIFIT TYPE



## DIN STANDARD CONNECTIONS


### M21512

METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)

公制内螺纹 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOL - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)




### M21513

METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

公制内螺纹 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOL - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm				
	DN	inch	Size			T	mm	B	A	C
M21513-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	21,9	1,7		14
M21513-03-14	5	3/16"	- 03	M 14x1,5	8	4,5	24,5	1,7		17
M21512-04-12	6	1/4"	- 04	M 12x1,5	6	3,0	21,1	2,2		17
M21513-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	22,1	1,7		17
M21513-04-16	6	1/4"	- 04	M 16x1,5	10	6,0	22,6	2,1		19
M21513-04-18	6	1/4"	- 04	M 18x1,5	12	7,0	21,9	2,3		22
M21512-05-14	8	5/16"	- 05	M 14x1,5	8	4,0	20,0	1,7		17
M21513-05-16	8	5/16"	- 05	M 16x1,5	10	6,0	22,6	2,1		19
M21513-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	21,9	2,3		22
M21512-06-16	10	3/8"	- 06	M 16x1,5	10	6,0	23,1	3,0		19
M21513-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	22,4	2,3		22
M21513-06-22	10	3/8"	- 06	M 22x1,5	15	9,3	25,0	2,3		27
M21512-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	29,0	2,9		22
M21513-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	25,4	2,3		27
M21513-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	26,1	2,5		32
M21512-10-18	16	5/8"	- 10	M 18x1,5	12	7,0	29,0	2,9		22
M21512-10-22	16	5/8"	- 10	M 22x1,5	15	9,5	26,5	2,4		27
M21513-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	26,0	2,5		32
M21513-10-30	16	5/8"	- 10	M 30x2	22	15,0	34,0	3,6		36
M21513-10-36	16	5/8"	- 10	M 36x2	28	20,0	30,5	3,8		41
M21512-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	31,1	3,6		32
M21513-12-30	19	3/4"	- 12	M 30x2	22	15,0	28,2	3,6		36
M21513-12-36	19	3/4"	- 12	M 36x2	28	20,0	28,3	3,8		41
M21512-16-30	25	1"	- 16	M 30x2	22	15,0	34,0	3,6		36
M21513-16-36	25	1"	- 16	M 36x2	28	19,8	29,4	3,8		41
M21513-16-45	25	1"	- 16	M 45x2	35	26,0	39,0	5,1		50
M21512-20-36	31	1.1/4"	- 20	M 36x2	28	19,8	35,5	5,0		41
M21513-20-45	31	1.1/4"	- 20	M 45x2	35	26,0	32,9	5,1		50
M21513-20-52	31	1.1/4"	- 20	M 52x2	42	32,0	32,5	5,1		60
M21512-24-45	38	1.1/2"	- 24	M 45x2	35	26,0	42,5	5,8		50
M21513-24-52	38	1.1/2"	- 24	M 52x2	42	32,0	32,8	5,1		60

# MULTIFIT TYPE



## DIN STANDARD CONNECTIONS

### M21612

METRIC O-RING FEMALE 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


公制内螺纹 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOS - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE PESANTE

DIN 20066 / ISO 12151-2 (DADO SPINATO)



### M21613

METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)


公制内螺纹 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)


DKOS - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE PESANTE

DIN 20066 / ISO 12151-2 (DADO PASSANTE)




PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm					
	DN	inch			Size	T	mm	B	A	C
M21613-03-14	5	3/16"	- 03	M 14x1,5	6	2,5	25,5	3,5		17
M21613-03-16	5	3/16"	- 03	M 16x1,5	8	3,2	21,9	3,4		19
M21613-04-14	6	1/4"	- 04	M 14x1,5	6	3,0	23,5	3,5		17
M21613-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	22,2	3,4		19
M21613-04-18	6	1/4"	- 04	M 18x1,5	10	4,0	28,0	3,0		22
M21613-04-20	6	1/4"	04	M 20x1,5	12	7,0	25,7	2,5		24
M21613-05-18	8	5/16"	- 05	M 18x1,5	10	5,5	28,0	3,0		22
M21613-05-20	8	5/16"	- 05	M 20x1,5	12	5,5	24,8	2,5		24
M21613-06-18	10	3/8"	- 06	M 18x1,5	10	7,0	28,5	3,0		22
M21613-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	25,3	2,5		24
M21613-06-22	10	3/8"	- 06	M 22x1,5	14	7,0	32,6	3,0		27
M21613-06-24	10	3/8"	- 06	M 24x1,5	16	7,0	32,0	3,0		30
M21612-08-20	12	1/2"	- 08	M 20x1,5	12	7,0	29,0	2,5		24
M21612-08-22	12	1/2"	- 08	M 22x1,5	14	7,0	27,5	2,5		27
M21613-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	26,7	3,0		30
M21613-08-30	12	1/2"	- 08	M 30x2	20	12,5	37,0	3,5		36
M21612-10-24	16	5/8"	- 10	M 24x1,5	16	9,3	29,5	4,0		30
M21613-10-30	16	5/8"	- 10	M 30x2	20	12,5	30,6	3,5		36
M21613-10-36	16	5/8"	- 10	M 36x2	25	15,0	40,0	4,5		41
M21612-12-24	19	3/4"	- 12	M 24x1,5	16	9,3	30,5	4,0		30
M21612-12-30	19	3/4"	- 12	M 30x2	20	12,5	33,5	2,2		36
M21613-12-36	19	3/4"	- 12	M 36x2	25	15,0	34,1	4,5		41
M21612-16-30	25	1"	- 16	M 30x2	20	12,5	34,5	2,2		36
M21612-16-36	25	1"	- 16	M 36x2	25	15,0	35,3	1,7		41
M21613-16-42	25	1"	- 16	M 42x2	30	19,8	35,4	6,3		50
M21613-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	37,5	8,0		60
M21613-24-52	38	1.1/2"	- 24	M 52x2	38	26,0	49,6	8,0		60



### M21013

METRIC FEMALE 60° CONE - DIN 20078/3863  
 公制 60° 锥内螺纹 - DIN 20078/3863  
 DKM 60° KONUS - DIN 20078/3863  
 FEMMINA METRICA CONO 60° - DIN 20078/3863

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H <sub>2</sub>
M21013-10-30	16	5/8"	- 10	M 30x1,5	20,0	20,0	8,1		36
M21013-12-30	19	3/4"	- 12	M 30x1,5	20,0	21,0	8,1		36
M21013-16-38	25	1"	- 16	M 38x1,5	26,0	22,8	7,6		46
M21013-20-45	31	1.1/4"	- 20	M 45x1,5	33,0	23,5	8,1		50
M21013-24-52	38	1.1/2"	- 24	M 52x1,5	40,0	25,0	8,1		60



### M21093

90° METRIC FEMALE SWEPT ELBOW 60° CONE - DIN 20078/3863  
 90° 公制 60° 锥内螺纹巨肘弯头 - DIN 20078/3863  
 DKM 90° BOGEN 60° KONUS - DIN 20078/3863  
 FEMMINA METRICA 90° CONO 60° - DIN 20078/3863

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>2</sub>
M21093-12-30	19	3/4"	- 12	M 30x1,5	20,0	61,5	8,1	54,5		36
M21093-16-38	25	1"	- 16	M 38x1,5	26,0	76,5	7,6	63,0		46
M21093-20-45	31	1.1/4"	- 20	M 45x1,5	33,0	92,0	8,1	81,0		50