


M22411



ORFS FEMALE - SAE J516 / ISO 12151-1 PULLBACK TYPE (CRIMPED BACK-NUT)
 ORFS 内螺纹 - SAE J516 / ISO 12151-1 回拉式 (带扣压-支撑螺母)
 ORFS IG - SAE J516 / ISO 12151-1 RÜCKZUGSAUSFÜHRUNG (VERPRESSTE MUTTER)
 FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE RETRAIBILE (DADO PRESSATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	H ₂
M22411-04-04	6	1/4"	- 04	9/16" - 18	4,0	27,5	8,0		13	19
M22411-04-06	6	1/4"	- 04	11/16" - 16	7,0	30,0	9,5		16	22
M22411-04-08	6	1/4"	- 04	13/16" - 16	9,3	34,5	11,0		19	24
M22411-05-04	8	5/16"	- 05	9/16" - 18	4,0	28,5	8,0		16	19
M22411-05-06	8	5/16"	- 05	11/16" - 16	7,0	30,5	9,5		16	22
M22411-06-04	10	3/8"	- 06	9/16" - 18	4,0	29,0	8,0		16	19
M22411-06-06	10	3/8"	- 06	11/16" - 16	7,0	31,1	9,5		16	22
M22411-06-08	10	3/8"	- 06	13/16" - 16	9,3	35,6	11,0		19	24
M22411-08-06	12	1/2"	- 08	11/16" - 16	7,0	31,9	9,5		19	22
M22411-08-08	12	1/2"	- 08	13/16" - 16	9,3	35,9	11,0		19	24
M22411-08-10	12	1/2"	- 08	1" - 14	11,5	38,4	13,5		24	30
M22411-08-12	12	1/2"	- 08	1.3/16" - 12	13,9	41,9	14,5		28	36
M22411-10-08	16	5/8"	- 10	13/16" - 16	9,3	36,0	11,0		24	24
M22411-10-10	16	5/8"	- 10	1" - 14	11,5	38,7	13,5		24	30
M22411-10-12	16	5/8"	- 10	1.3/16" - 12	13,9	42,0	14,5		28	36
M22411-12-10	19	3/4"	- 12	1" - 14	11,5	41,0	13,5		28	30
M22411-12-12	19	3/4"	- 12	1.3/16" - 12	13,9	43,5	14,5		28	36
M22411-12-16	19	3/4"	- 12	1.7/16" - 12	19,8	45,5	15,0		36	41
M22411-16-12	25	1"	- 16	1.3/16" - 12	13,9	45,8	14,5		36	36
M22411-16-16	25	1"	- 16	1.7/16" - 12	19,8	46,3	15,0		36	41
M22411-16-20	25	1"	- 16	1.11/16" - 12	26,0	49,5	14,8		41	50
M22411-20-20	31	1.1/4"	- 20	1.11/16" - 12	26,0	49,0	14,8		41	50
M22411-24-24	38	1.1/2"	- 24	2" - 12	32,0	54,0	15,8		50	60

MULTIFIT TYPE



SAE STANDARD CONNECTIONS

M27411


ORFS FEMALE - SAE J516 / ISO 12151-1 SHORT TYPE (CRIMPED BACK-NUT)

ORFS 内螺纹 - SAE J516 / ISO 12151-1 短型 (带扣压-支撑螺母)

ORFS VERPRESSTE MUTTER - SAE J516 / ISO 12151-1

KURZE AUSFÜHRUNG (CRIMPED BACK-NUT)

FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE CORTA (DADO PRESSATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	H ₂
M27411-04-04	6	1/4"	- 04	9/16" - 18	4,0	20,5	8,0		13	19
M27411-04-06	6	1/4"	- 04	11/16" - 16	7,0	22,0	9,5		16	22
M27411-05-06	8	5/16"	- 05	11/16" - 16	7,0	25,5	9,5		16	22
M27411-06-06	10	3/8"	- 06	11/16" - 16	7,0	26,0	9,5		16	22
M27411-06-08	10	3/8"	- 06	13/16" - 16	9,3	25,0	11,0		19	24
M27411-08-08	12	1/2"	- 08	13/16" - 16	9,3	25,5	11,0		19	24
M27411-08-10	12	1/2"	- 08	1" - 14	11,5	26,5	13,5		24	30
M27411-08-12	12	1/2"	- 08	1.3/16" - 12	13,9	29,0	14,5		28	36
M27411-10-10	16	5/8"	- 10	1" - 14	11,5	26,5	13,5		24	30
M27411-10-12	16	5/8"	- 10	1.3/16" - 12	13,9	29,0	14,5		28	36
M27411-12-12	19	3/4"	- 12	1.3/16" - 12	13,9	30,5	14,5		28	36
M27411-16-16	25	1"	- 16	1.7/16" - 12	19,8	33,0	15,0		36	41