


Raccordi Mod. 6610

Senza alcun riferimento sono sempre assemblabili con i Mod. 1631; 1635.




INGOMBRI								
Mod.	A	C	F	M	O	V	W	Peso (g)
6610 4-M5	4	5	9	19	9	5,1	Ø 9	9
6610 4-M6	4	5	9	19	9	5,1	Ø 9	8 •
6610 4-1/8	4	7,5	9	21,5	14,5	9,8	Ø 14	14
6610 5-M5	5	5	10	20	9	5,1	Ø 9	9
6610 5-M6	5	5	10	20	9	5,1	Ø 9	8 •
6610 5-1/8	5	8	10	23	14,5	9,8	Ø 14	16
6610 6-M5	6	6,5	12,7	22,5	9	5,1	Ø 10	12
6610 6-M6	6	6,5	12,7	22,5	9	5,1	Ø 10	12 •
6610 6-1/8	6	8	12,7	24	14,5	9,8	Ø 14	16
6610 6-1/4	6	10	12,7	26	14,5	13,2	Ø 18	19
6610 8-1/8	8	8	14,2	25,5	14,5	9,8	Ø 14	19
6610 8-1/4	8	10	14,2	27,5	14,5	13,2	Ø 18	22
6610 8-3/8	8	11	14,2	28,5	14,5	16,7	Ø 21	23
6610 10-1/4	10	8,8	16,5	29	14,5	13,2	Ø 18	22 *
6610 10-3/8	10	10,3	16,5	30,5	14,5	16,7	Ø 21	23 *
6610 12-1/2	12	12,8	16,5	32	14,5	21	Ø 26	37 *

• = assemblabili solo con Mod. SCU, SVU, SCO... M5
 * = assemblabili solo con Mod. 1635

Raccordi Mod. 6811

Sprint®



INGOMBRI							
Mod.	G	D	H	T	L	SW	Peso (g)
6811 4-M5	4	M5	4	16,5	24,5	8	3 *
6811 4-1/8	4	G1/8	5,5	16,5	27,8	12	10
6811 5-1/8	5	G1/8	5,5	18	29,3	12	9
6811 5-1/4	5	G1/4	7	18	31	14	11
6811 6-1/8	6	G1/8	5,5	18	29,3	12	10
6811 6-1/4	6	G1/4	7	18	31	14	12
6811 8-1/8	8	G1/8	5,5	20,5	31,8	12	12
6811 8-1/4	8	G1/4	7	20,5	33,5	14	13
6811 10-1/4	10	G1/4	7	23	36	14	16
6811 10-3/8	10	G3/8	8	23	37,3	19	25
6811 12-3/8	12	G3/8	8	24	38,3	19	25
6811 14-1/2	14	G1/2	9	28	44	22	39

* = con O-Ring montato