

Art.	Serie Series Série	Bocche Hoses Orifices	Adescamento Priming Amorçage (m)	Giri/min. max Max r.p.m. Tours/min. max	PORTATA - CAPACITY DEBIT (LT/MIN)												
					1400 giri/min. 1400 r.p.m. 1400 tours/min.				1900 giri/min. 1900 r.p.m. 1900 tours/min.				2800 giri/min. 2800 r.p.m. 2800 tours/min.				
					H (m)	1	5	10	15	1	5	10	15	1	10	20	30
540	I 20	3/4" M	6	2900	Q	9	4			16	11	4		32	21	9	
					HP	0.1	0.1			0.1	0.1	0.2		0.2	0.3	0.3	
541	I 25	1" M	6	2900	Q	53	38	16		72	61	47	31	97	85	70	50
					HP	0.2	0.2	0.3		0.6	0.6	0.7	0.7	1.2	1.4	1.6	1.8
542	I 30	1"1/2 M	6	2900	Q	89	71	43	9	123	108	90	70	166	150	129	105
					HP	0.5	0.6	0.7	0.8	0.9	0.9	1	1.1	2.6	2.9	3.2	3.5
543	I 35	1"1/2 M	6	2900	Q	89	71	43	9	123	108	90	70	166	150	129	105
					HP	0.5	0.6	0.7	0.8	0.9	0.9	1	1.1	2.6	2.9	3.2	3.5
544	I 40	1"1/2 M	6	2900	Q	149	119	78	32	192	168	139	110	258	234	203	167
					HP	0.6	0.7	0.8	1	1.5	1.6	1.8	1.9	3.7	4.1	4.6	5
545	I 50	2" M	6	1900	Q	262	227	180	129	360	333	299	265				
					HP	1.4	1.5	1.7	1.9	3.2	3.5	3.8	4.1				

Caratteristiche riferite al funzionamento con acqua. Ci riserviamo la facoltà di apportare modifiche senza obbligo di preavviso / Performances referred to operation with water We reserve the right to make modifications without prior notice / Caracteristiques référées au fonctionnement avec eau. Sous réserve de modifications sans avis préalable