

DIN 133

• Utilizzabili a percussione con mazza o martello pneumatico

art.	mm					
000580024	58	24	177	52,0	15,0	0,25
000580027	58	27	180	58,0	16,0	0,32
000580030	58	30	190	66,0	17,0	0,43
000580032	58	32	190	68,0	17,0	0,45
000580036	58	36	215	78,0	19,0	0,70
000580041	58	41	235	90,0	19,0	0,90
000580046	58	46	255	100,0	21,0	1,24
000580050	58	50	275	110,0	21,0	1,56
000580055	58	55	300	120,0	23,0	2,00
000580060	58	60	320	130,0	23,0	2,61
000580065	58	65	342	142,0	28,0	3,50
000580070	58	70	375	156,0	30,0	4,30
000580075	58	75	375	164,0	30,0	4,50
000580080	58	80	408	175,0	33,0	5,80
000580085	58	85	408	175,0	33,0	5,80
000580090	58	90	445	197,0	38,0	8,10
000580095	58	95	445	197,0	38,0	7,96
000580100	58	100	485	215,0	45,0	11,60
000580105	58	105	485	215,0	45,0	11,40
000580110	58	110	510	235,0	47,0	13,50
000580115	58	115	510	235,0	47,0	13,50
000580120	58	120	545	255,0	50,0	17,30
000580125	58	125	545	255,0	50,0	17,50
000580130	58	130	575	275,0	55,0	19,40
000580135	58	135	575	275,0	55,0	19,30
* 000580140	58	140	575	275,0	55,0	19,20
* 000580145	58	145	640	305,0	60,0	28,20
* 000580150	58	150	640	305,0	60,0	27,80
* 000580155	58	155	640	305,0	60,0	27,40
* 000580160	58	160	640	305,0	60,0	27,00
* 000580165	58	165	715	342,0	70,0	39,90
* 000580170	58	170	715	342,0	70,0	39,40
* 000580175	58	175	715	342,0	70,0	39,00
* 000580180	58	180	715	342,0	70,0	38,50
* 000580185	58	185	715	342,0	70,0	38,00
* 000580190	58	190	800	392,0	78,0	53,70
* 000580195	58	195	800	392,0	78,0	53,00
* 000580200	58	200	800	392,0	78,0	52,60
* 000580210	58	210	800	392,0	78,0	52,20
* 000580220	58	220	800	392,0	78,0	51,60
* 000580230	58	230	800	392,0	78,0	51,50

