

DIN 7444

- Utilizzabili a percussione con mazza o martello pneumatico

art.	mm	L mm	Ø mm	S mm	kg
000780024	24	162	42,0	15,0	0,24
000780027	27	180	47,0	16,0	0,27
000780030	30	190	54,0	17,0	0,37
000780032	32	190	54,0	17,0	0,35
000780036	36	205	60,0	19,0	0,53
000780041	41	225	66,0	20,0	0,70
000780046	46	235	75,0	22,0	0,93
000780050	50	250	80,0	24,0	1,15
000780055	55	265	88,0	25,0	1,40
000780060	60	275	94,0	26,0	1,60
000780065	65	295	104,0	28,0	2,00
000780070	70	325	110,0	33,0	2,90
000780075	75	325	115,0	33,0	2,70
000780080	80	350	126,0	36,0	3,90
000780085	85	350	130,0	36,0	3,80
000780090	90	390	152,0	39,0	5,10
000780095	95	390	152,0	39,0	4,80
000780100	100	420	155,0	43,0	6,60
000780105	105	420	172,0	45,0	6,20
000780110	110	450	172,0	47,0	8,20
000780115	115	450	172,0	47,0	7,60
000780120	120	490	194,0	53,0	9,80
000780125	125	480	194,0	53,0	9,00
000780130	130	520	205,0	57,0	13,50
000780135	135	520	205,0	60,0	13,00
* 000780140	140	520	205,0	60,0	12,70
* 000780145	145	580	230,0	62,0	19,20
* 000780150	150	580	230,0	62,0	19,00
* 000780155	155	580	230,0	62,0	17,80
* 000780160	160	650	270,0	66,0	19,00
* 000780165	165	650	270,0	66,0	28,00
* 000780170	170	650	270,0	66,0	27,30
* 000780175	175	650	270,0	66,0	26,20
* 000780180	180	650	270,0	66,0	26,00
* 000780185	185	695	295,0	71,0	35,00
* 000780190	190	695	295,0	71,0	33,60
* 000780195	195	695	295,0	71,0	33,00
* 000780200	200	695	295,0	71,0	32,10
* 000780210	210	740	325,0	76,0	40,60
* 000780215	215	740	325,0	76,0	38,90
* 000780220	220	740	325,0	76,0	36,50
* 000780230	230	740	325,0	76,0	34,65

