



PUNTE

■ **Art. 2.1**

**PUNTE CON INSERTO IN CARBURO DI TUNGSTENO
STANDARD QUALITY**

CARATTERISTICHE

Per forare a rotazione e rotopercolazione: muro, mattoni, pietra, marmo, cemento.

SERIE CORTA - DIN 8039 EURONORM

ESECUZIONE ZINCATO

PACKAGE:

Imballo singolo in bustine di plastica.

COD.	dimensioni			
	Ø mm	Ø d1 mm	L1 mm	d2xL2 mm
3	1/8	2,5	65	-
3,5	9/64	3,2	65	-
4	5/32	3,2	75	-
4,5	11/64	4	75	-
5	3/16	4	85	-
5,5	7/32	4,8	85	-
6	15/64	4,8	100	-
6,5	1/4	4,8	100	-
7	9/32	5,5	100	-
7,5	19/64	5,5	100	-
8	5/16	6,2	120	-
8,5	21/64	6,2	120	-
9	23/64	7,5	120	-
10	3/8	7,5	120	-
11	7/16	8,5	150	-
12	15/32	8,5	150	-
13	1/2	10	150	-
14	9/16	10	150	-
15	19/32	12	150	10x30
16	5/8	12	150	10x30
18	23/32	13	160	10x30
20	25/32	16	160	13x30
22	7/8	16	160	13x30
24	15/16	18,5	160	13x30
25	1"	18,5	160	13x30
26	1"1/32	21	160	13x30
28	1"1/8	23	200	13x30
30	1"3/16	23	200	13x30

