


# Compressori d'aria con trasmissione a cinghia

## Belt driven air compressors



**AB 50**  
**AB 100**  
**AB 150**  
**AB 200**



	L	P	H
<b>AB 50/245</b>	1010/46.6	360/14	730/27.5
<b>AB 100/245-335</b>	1100/42.9	400/15.6	830/32.4
<b>AB 150/245-335</b>	1360/53	540/21	1060/41.3
<b>AB 200/245-335</b>	1460/56.9	640/24.9	1140/44.5


CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m <sup>3</sup> /h	bar	psi	HP	kW	kW	min-1	Kg	m <sup>3</sup>
AB 50-245	230/50/1▲X	1431641000	50	72	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	50	0.263
AB 100-245	230/50/1▲X	1432002000	100	72	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	62	0.393
AB 150-245	230/50/1▲X	1434002000	150	73	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	86	0.831
AB 200-245	230/50/1▲X	1436002000	200	73	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	100	1.128
AB 100-335	230/50/1▲X	1432011000	100	76	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	64	0.393
AB 150-335	230/50/1▲X	1434011000	150	77	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	88	0.831
AB 200-335	230/50/1▲X	1436011000	200	77	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	102	1.128



**AB 150**  
**AB 200**



	L	P	H
<b>AB 150</b>	1360/53.5	540/21	1060/41.3
<b>AB 200</b>	1460/57.5	640/24.9	1140/44.4


CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m <sup>3</sup> /h	bar	psi	HP	kW	kW	min-1	Kg	m <sup>3</sup>
AB 150-410	400/50/3■	1464531000	150	76	99	AB 410	2/1	400	14	24	10	145	3	2,25	3	1210	95	0.831
AB 200-410	400/50/3■	1465621000	200	76	99	AB 410	2/1	400	14	24	10	145	3	2,25	3	1210	109	0.895
AB 200-480	400/50/3■	1465040000	200	76	99	AB 450	2/2	480	17	29	10	145	4	3	4	1200	140	0.895
AB 200-510	400/50/3■	1465631000	200	78	99	AB 510	2/1	482	17	29	10	145	4	3	4	1470	125	0.895
AB 200-530	400/50/3■	1465410000	200	71	95	AB 671	2/2	520	18,3	31,2	10	145	4	3	4	800	150	0.895



**AB 300**



CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m <sup>3</sup> /h	bar	psi	HP	kW	kW	min-1	Kg	m <sup>3</sup>
AB 300-480	400/50/3■	1466010000	270	76	99	AB 450	2/2	480	17	29	10	145	4	3	4	1200	173	1.242
AB 300-510	400/50/3■	1466571000	270	78	99	AB 510	2/1	482	17	29	10	145	4	3	4	1470	170	1.242
AB 300-530	400/50/3■	1466440000	270	71	95	AB 671	2/2	520	18,3	31,2	10	145	4	3	4	800	186	1.242
AB 300-550	400/50/3■	1466020000	270	75	99	AB 550	2/2	550	19,4	33	10	145	5,5	4,1	5,5	1400	175	1.242
AB 300-670	400/50/3■	1466420000	270	74	97	AB 671	2/2	650	23	39	10	145	5,5	4,1	5,5	1000	180	1.242
AB 300-850	400/50/3■	1466430000	270	76	99	AB 851	2/2	830	29,3	50	10	145	7,5	5,5	7,5	1280	185	1.242