



TN 92

- Raccordo di estremità dritto
- Gerade Einschraubverschraubungen
- Male Stud Couplings
- Union simple mâle

Filettatura:
Gas cilindrica
Metrica cilindrica

Einschraubgewinde:
Withworth-Rohrgewinde zylindrisch
Metrisches Feingewinde zylindrisch

Thread:
B.S.P. parallel
Metric parallel

Filetage:
Gaz cylindrique
Métrique cylindrique

Forma B DIN 3852 Foglio 2

Form B DIN 3852 Teil 2

Type B DIN 3852 Part 2

Forme B DIN 3852 Partie 2

Serie Reihe Series Série	Ø Tubo Rohr AD Tube O.D. Ø Tube d _t	PN PE	b)		b)	CH1	R				M				Peso Gewicht Weight Poids kg.×100 P.
			I	L			L1	Ø F	Ø N	CH2	Simbolo di ordinazione Bestell-Nr. Part. No. Références	Ø F	Ø N	CH2	
L	6	315	8	23	8,5	14	1/8"	14	14	TN 92 - 6 LR	10 × 1	14	14	TN 92 - 6 LM	2,5
	8		12	25	10	17	1/4"	18	19	TN 92 - 8 LR	12 × 1,5	17	17	TN 92 - 8 LM	4,5
	8		12	26	11,5	17	3/8"	22	22	TN 92 - 8 LR 3/8"	-	-	-	-	6,0
	10		12	26	11	19	1/4"	18	19	TN 92 - 10 LR	14 × 1,5	19	19	TN 92 - 10 LM	4,7
	10		12	27	12,5	19	3/8"	22	22	TN 92 - 10 LR 3/8"	-	-	-	-	6,0
	12		12	27	12	22	1/4"	18	19	TN 92 - 12 LR 1/4"	-	-	-	-	6,1
	12		12	27	12,5	22	3/8"	22	22	TN 92 - 12 LR	16 × 1,5	21	22	TN 92 - 12 LM	6,5
	12		14	28	13	22	1/2"	26	27	TN 92 - 12 LR 1/2"	-	-	-	-	9,5
	15		14	29	14	27	1/2"	26	27	TN 92 - 15 LR	18 × 1,5	23	24	TN 92 - 15 LM	11,5
	18		14	31	14,5	32	1/2"	26	27	TN 92 - 18 LR	22 × 1,5	27	27	TN 92 - 18 LM	13,0
	22		16	33	16,5	36	3/4"	32	32	TN 92 - 22 LR	26 × 1,5	31	32	TN 92 - 22 LM	18,0
	28		18	34	17,5	41	1"	39	41	TN 92 - 28 LR	33 × 2	39	41	TN 92 - 28 LM	25,0
35	20	39	17,5	50	1" 1/4	49	50	TN 92 - 35 LR	42 × 2	49	50	TN 92 - 35 LM	41,0		
42	22	42	19	60	1" 1/2	55	55	TN 92 - 42 LR	48 × 2	55	55	TN 92 - 42 LM	46,0		
S	6	630	12	28	13	17	1/4"	18	19	TN 92 - 6 SR	12 × 1,5	17	17	TN 92 - 6 SM	5,2
	8		12	30	15	19	1/4"	18	19	TN 92 - 8 SR	14 × 1,5	19	19	TN 92 - 8 SM	6,0
	10		12	31	15	22	3/8"	22	22	TN 92 - 10 SR	16 × 1,5	21	22	TN 92 - 10 SM	9,0
	12		12	33	17	24	3/8"	22	22	TN 92 - 12 SR	18 × 1,5	23	24	TN 92 - 12 SM	10,2
	12		14	34	17,5	24	1/2"	26	27	TN 92 - 12 SR 1/2"	-	-	-	-	13,5
	14		14	37	19	27	1/2"	26	27	TN 92 - 14 SR	20 × 1,5	25	27	TN 92 - 14 SM	15,2
	16	14	37	18,5	30	1/2"	26	27	TN 92 - 16 SR	22 × 1,5	27	27	TN 92 - 16 SM	16,0	
	20	16	42	20,5	36	3/4"	32	32	TN 92 - 20 SR	27 × 2	32	32	TN 92 - 20 SM	27,0	
	25	18	47	23	46	1"	39	41	TN 92 - 25 SR	33 × 2	39	41	TN 92 - 25 SM	49,0	
	30	20	50	23,5	50	1" 1/4	49	50	TN 92 - 30 SR	42 × 2	49	50	TN 92 - 30 SM	66,0	
38	22	57	26	60	1" 1/2	55	55	TN 92 - 38 SR	48 × 2	55	55	TN 92 - 38 SM	92,0		

- Le dimensioni di ingombro si intendono a raccordo chiuso.
- Baumaße sind ca.-Maße bei angezogener Überwurfmutter.

- Overall sizes are with closed fitting.
- Les dimensions d'encombrement s'entendent raccord monté.
b) TN 92-15 LM - I=12; L1 = 13.5

a) Fattore di sicurezza = 2 (Filettatura Metrica cilindrica)

Sicherheitsfaktor = 2 (Einschraubgewinde Metrisches Feingewinde zylindrisch)

Safety factor = 2 (Thread Metric parallel)

Facteur de sécurité = 2 (Filetage Métrique cylindrique)