

MULTIFIT TYPE



BS STANDARD CONNECTIONS


M20542

45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

45° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)

DKR 45° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)

FEMMINA GAS 45° CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)




M20543

45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)

45° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)

DRK 45° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)

FEMMINA GAS 45° CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M20542-03-02	5	3/16"	- 03	1/8" - 28	3,1	31,0	4,4	15,0		14
M20543-03-04	5	3/16"	- 03	1/4" - 19	4,0	35,5	5,4	14,5		19
M20542-04-02	6	1/4"	- 04	1/8" - 28	3,1	35,5	4,4	14,5		14
M20543-04-04	6	1/4"	- 04	1/4" - 19	4,0	36,0	5,4	15,0		19
M20543-04-06	6	1/4"	- 04	3/8" - 19	7,0	37,5	6,0	16,0		19
M20542-05-04	8	5/16"	- 05	1/4" - 19	4,0	35,5	5,4	16,0		19
M20543-05-06	8	5/16"	- 05	3/8" - 19	7,0	38,0	6,0	13,5		22
M20543-06-06	10	3/8"	- 06	3/8" - 19	7,0	42,0	6,0	15,0		22
M20543-06-08	10	3/8"	- 06	1/2" - 14	9,3	42,5	6,5	16,0		27
M20542-08-06	12	1/2"	- 08	3/8" - 19	7,1	52,0	6,0	20,0		22
M20543-08-08	12	1/2"	- 08	1/2" - 14	9,3	49,5	6,5	17,0		27
M20542-08-10	12	1/2"	- 08	5/8" - 14	12,1	54,5	10,2	22,5		28
M20542-08-12	12	1/2"	- 08	3/4" - 14	15,0	57,0	9,0	25,0		32
M20542-10-10	16	5/8"	- 10	5/8" - 14	12,5	63,0	10,2	26,0		28
M20542-10-12	16	5/8"	- 10	3/4" - 14	15,0	64,0	9,0	27,0		32
M20542-12-08	19	3/4"	- 12	1/2" - 14	9,3	55,5	6,5	22,5		27
M20542-12-12	19	3/4"	- 12	3/4" - 14	15,5	70,5	9,0	28,5		32
M20542-12-16	19	3/4"	- 12	1" - 11	19,8	72,5	10,5	30,0		38
M20542-16-16	25	1"	- 16	1" - 11	19,8	91,0	10,5	36,5		38