


MULTIFIT TYPE



BS STANDARD CONNECTIONS


M20512

BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 BSP 内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)
 FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)




M20513


BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)
 BSP 内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)
 DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)
 FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H ₂
M20512-03-02	5	3/16"	- 03	1/8" - 28	3,1	14,8	4,4		14
M20513-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	5,4		19
M20512-04-02	6	1/4"	- 04	1/8" - 28	3,1	15,5	4,4		14
M20513-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,0	5,4		19
M20513-04-06	6	1/4"	- 04	3/8" - 19	7,0	19,1	6,0		22
M20512-05-04	8	5/16"	- 05	1/4" - 19	4,1	17,5	4,2		19
M20513-05-06	8	5/16"	- 05	3/8" - 19	7,0	19,1	6,0		22
M20513-05-08	8	5/16"	- 05	1/2" - 14	9,3	20,5	6,5		27
M20512-06-04	10	3/8"	- 06	1/4" - 19	4,1	18,1	4,2		19
M20513-06-06	10	3/8"	- 06	3/8" - 19	7,0	19,6	6,0		22
M20513-06-08	10	3/8"	- 06	1/2" - 14	9,3	20,0	6,5		27
M20512-08-06	12	1/2"	- 08	3/8" - 19	7,1	20,9	6,0		22
M20513-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5		27
M20512-08-10	12	1/2"	- 08	5/8" - 14	12,1	21,9	10,2		28
M20512-08-12	12	1/2"	- 08	3/4" - 14	15,0	23,4	9,0		32
M20512-10-08	16	5/8"	- 10	1/2" - 14	9,8	24,0	6,5		27
M20512-10-10	16	5/8"	- 10	5/8" - 14	12,5	21,7	10,2		28
M20512-10-12	16	5/8"	- 10	3/4" - 14	15,0	23,2	9,0		32
M20512-12-08	19	3/4"	- 12	1/2" - 14	9,8	25,0	6,5		27
M20512-12-12	19	3/4"	- 12	3/4" - 14	15,0	24,5	9,0		32
M20512-12-16	19	3/4"	- 12	1" - 11	19,8	26,0	10,5		38
M20512-16-12	25	1"	- 16	3/4" - 14	15,0	25,5	9,0		32
M20512-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,5		38




M20812
 BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 BSP O型圈内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 60° KONUS MIT O-RING -
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6 GESTIFTETE MUTTER)
 FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)




M20813
 BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)
 BSP O型圈内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)
 DKOR 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6 HINTERLEGTE MUTTER)
 FEMMINA GAS CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H ₂
M20813-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	4,9		19
M20813-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,5	4,9		19
M20812-06-04	10	3/8"	- 06	1/4" - 19	4,0	18,1	4,9		19
M20813-06-06	10	3/8"	- 06	3/8" - 19	7,0	20,4	6,1		22
M20813-06-08	10	3/8"	- 06	1/2" - 14	9,3	21,0	6,5		27
M20813-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5		27
M20812-10-10	16	5/8"	- 10	5/8" - 14	12,5	22,1	9,7		28
M20812-12-12	19	3/4"	- 12	3/4" - 14	15,0	25,0	8,5		32
M20812-16-12	25	1"	- 16	3/4" - 14	15,0	26,0	8,5		32
M20812-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,6		38
M20812-16-20	25	1"	- 16	1.1/4" - 11	26,1	30,8	10,5		50
M20812-20-16	31	1.1/4"	- 20	1" - 11	19,8	29,0	10,5		38
M20812-20-20	31	1.1/4"	- 20	1.1/4" - 11	26,0	31,5	10,5		50
M20812-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,1	29,5	12,5		60
M20812-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	31,5	10,5		50
M20812-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	30,5	12,5		60
M20812-24-32	38	1.1/2"	- 24	2" - 11	42,0	30,0	16,1		70
M20812-32-32	51	2"	- 32	2" - 11	42,0	31,9	16,1		70



M22512
JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带止推金属丝螺母)
 DKJ 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)



M22513
JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)
 JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带滑套螺母)
 DKJ 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H ₂
M22513-03-04	5	3/16"	- 03	7/16" - 20	3,0	15,1	9,0		15
M22512-03-05	5	3/16"	- 03	1/2" - 20	4,0	15,5	9,2		17
M22512-04-04	6	1/4"	- 04	7/16" - 20	4,0	15,5	8,2		17
M22512-04-05	6	1/4"	- 04	1/2" - 20	4,0	15,8	9,2		17
M22513-04-06	6	1/4"	- 04	9/16" - 18	4,0	16,5	9,8		19
M22512-05-04	8	5/16"	- 05	7/16" - 20	4,0	15,5	8,2		17
M22512-05-05	8	5/16"	- 05	1/2" - 20	5,5	16,0	9,2		17
M22512-05-06	8	5/16"	- 05	9/16" - 18	7,0	15,7	9,7		19
M22513-05-08	8	5/16"	- 05	3/4" - 16	5,5	16,7	10,7		22
M22512-06-05	10	3/8"	- 06	1/2" - 20	5,5	16,6	9,5		17
M22512-06-06	10	3/8"	- 06	9/16" - 18	7,0	16,1	9,2		19
M22513-06-08	10	3/8"	- 06	3/4" - 16	7,0	17,3	10,7		22
M22513-06-10	10	3/8"	- 06	7/8" - 14	9,3	18,1	12,4		27
M22512-08-08	12	1/2"	- 08	3/4" - 16	9,3	19,9	10,2		22
M22513-08-10	12	1/2"	- 08	7/8" - 14	9,3	18,5	12,4		27
M22513-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	21,8	13,8		32
M22512-10-10	16	5/8"	- 10	7/8" - 14	12,5	19,9	12,3		27
M22513-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	21,7	13,8		32
M22512-12-08	19	3/4"	- 12	3/4" - 16	9,3	21,5	10,2		22
M22512-12-10	19	3/4"	- 12	7/8" - 14	12,5	21,5	12,3		27
M22512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	22,5	14,2		32
M22512-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	23,1	14,8		36
M22512-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	23,0	15,2		38
M22512-16-12	25	1"	- 16	1.1/16" - 12	15,0	23,3	14,4		32
M22512-16-16	25	1"	- 16	1.5/16" - 12	19,8	23,8	15,2		38
M22512-16-20	25	1"	- 16	1.5/8" - 12	26,0	29,8	16,2		50
M22512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	30,0	16,2		50
M22512-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	35,0	18,8		60
M22512-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	35,0	18,8		60
M22512-32-24	51	2"	- 32	1.7/8" - 12	32,0	37,0	18,8		60
M22512-32-32	51	2"	- 32	2.1/2" - 12	44,0	35,4	24,0		75