


M24011

JIS METRIC FEMALE 60° CONE SEAT (KOMATSU) JIS B 8363 (CRIMPED-BACK NUT)
 JIS 公制内螺纹 60° 锥形底座 (小松标准) JIS B 8363 (扣压-支撑螺母)
 DK KOMATSU MIT 60° KONUS (NACH JIS B 8363, PRESSMUTTER)
 FEMMINA METRICA GIAPPONESE CONO 60° TIPO KOMATSU JIS B 8363 (DADO PRESSATO)



M24012

JIS METRIC FEMALE 60° CONE SEAT (KOMATSU) JIS B 8363 (THRUST-WIRE NUT)
 JIS 公制内螺纹 60° 锥形底座 (小松标准) JIS B 8363 (带止推金属丝螺母)
 DK KOMATSU MIT 60° KONUS (NACH JIS B 8363, GESTIFTETE MUTTER)
 FEMMINA METRICA GIAPPONESE CONO 60° TIPO KOMATSU JIS B 8363 (DADO SPINATO)

PART. REF.	HOSE BORE		THREAD	DIMENSIONS mm						
	DN	inch		Size	T	B	A	C	H ₁	H ₂
M24011-04-14	6	1/4"	- 04	M 14x1,5	4,0	23,0	10,5		19	19
M24011-04-18	6	1/4"	- 04	M 18x1,5	4,0	22,6	11,5		24	24
M24011-05-16	8	5/16"	- 05	M 16x1,5	5,5	22,5	9,3		21	21
M24011-06-14	10	3/8"	- 06	M 14x1,5	4,0	23,6	10,5		19	19
M24011-06-18	10	3/8"	- 06	M 18x1,5	7,0	23,6	11,5		24	24
M24011-08-22	12	1/2"	- 08	M 22x1,5	9,3	24,9	14,0		27	27
M24011-10-24	16	5/8"	- 10	M 24x1,5	12,5	26,7	15,1		32	32
M24011-12-30	19	3/4"	- 12	M 30x1,5	15,0	31,5	18,3		36	36
M24011-16-33	25	1"	- 16	M 33x1,5	19,8	33,3	21,3		41	41
M24011-20-36	31	1.1/4"	- 20	M 36x1,5	19,8	41,0	20,0		46	46
M24012-24-42	38	1.1/2"	- 24	M 42x1,5	26,0	44,0	18,8		55	55