



Raccordi Mod. 6522

Modello girevole con O-Ring montato



INGOMBRI										
Mod.	A	D	C	E	F	H	M	SW	SW1	Peso (g)
6522 4-M5	4	M5	3,5	12,5	9	4	17,5	8	8	12
6522 4-1/8	4	G1/8	3,5	14,5	9	6	17,5	8	12	15
6522 4-1/4	4	G1/4	3,5	15,5	9	7	17,5	8	15	25
6522 5-M5	5	M5	5,5	12,5	10	4	20,5	9	8	13
6522 6-M5	6	M5	4	13	12,7	4	20	9	10	14
6522 6-1/8	6	G1/8	4	15	12,7	6	20	9	12	19
6522 6-1/4	6	G1/4	4	16	12,7	7	20	9	15	27
6522 8-1/8	8	G1/8	5	16	14,2	6	22,5	11	12	22
6522 8-1/4	8	G1/4	5	17	14,2	7	22,5	11	15	28
6522 8-3/8	8	G3/8	5	17	14,2	7	22,5	11	19	45
6522 10-1/4	10	G1/4	5,8	19,5	16,5	7	26	13	15	41
6522 10-3/8	10	G3/8	5,8	19,5	16,5	7	26	13	19	45
6522 12-1/4	12	G1/4	7,3	20	19,5	7	26,5	15	17	51
6522 12-3/8	12	G3/8	7,3	20,5	19,5	7	26,5	15	19	56

Raccordi Mod. S6500
Sprint®


INGOMBRI										
Mod.	A	D	C	E	F	H	M	SW	SW1	Peso (g)
S6500 4-1/8	4	R1/8	3,5	8,5	9	7,5	17,5	8	9	9
S6500 4-1/4	4	R1/4	5	11,5	9	12	19	9	13	13
S6500 5-1/8	5	R1/8	5,5	8,5	10	7,5	20,5	9	13	13
S6500 5-1/4	5	R1/4	5,5	11,5	10	12	20,5	9	17	17
S6500 6-1/8	6	R1/8	4	9	12,7	7,5	20	9	15	15
S6500 6-1/4	6	R1/4	4	11,5	12,7	12	20	9	16	16
S6500 8-1/8	8	R1/8	5	10,5	14,2	6,5	22,5	11	18	18
S6500 8-1/4	8	R1/4	5	11,5	14,2	12,5	22,5	11	21	21
S6500 8-3/8	8	R3/8	7	13	14,2	11,5	24,5	12	25	25
S6500 10-1/4	10	R1/4	5,8	13	16,5	11,5	26	13	33	33
S6500 10-3/8	10	R3/8	5,8	13	16,5	12	26	13	33	33
S6500 12-1/4	12	R1/4	7,3	14,5	19,5	11	26,5	15	46	46
S6500 12-3/8	12	R3/8	7,3	13,5	19,5	11,5	26,5	15	39	39