

| TIPO TYPE                         |                                  | HP  | GIRI<br>R.p.m.<br>Tours | Bocche<br>Hoses<br>Orifices | Adescam.<br>Priming<br>Amorçage<br>(m) | Hmax<br>(m) | PORTATA - CAPACITY<br>DEBIT (LT/MIN) |     |      |      |      |      |
|-----------------------------------|----------------------------------|-----|-------------------------|-----------------------------|----------------------------------------|-------------|--------------------------------------|-----|------|------|------|------|
| Monofase - 1 phase<br>230 V 50 Hz | Trifase - 3 phase<br>400 V 50 Hz |     |                         |                             |                                        |             | 1 m                                  | 5 m | 10 m | 15 m | 20 m | 30 m |
| Art. 700 - ALM 20                 | Art. 710 - ALT 20                | 0.5 | 2800                    | 3/4" M                      | 6                                      | 24          | 28                                   | 23  | 17   | 11   | 5    |      |
| Art. 700 L - ALM 20 L             | Art. 710 L - ALT 20 L            | 0.2 | 1400                    | 3/4" M                      | 6                                      | 6           | 11                                   | 2   |      |      |      |      |
| Art. 701 - ALM 25                 | Art. 711 - ALT 25                | 0.6 | 1400                    | 1" M                        | 6                                      | 12          | 43                                   | 28  | 8    |      |      |      |
| Art. 702 - ALM 30                 | Art. 712 - ALT 30                | 2   | 2800                    | 1" M                        | 6                                      | 42          | 89                                   | 80  | 70   | 59   | 48   | 26   |
| Art. 704 - ALM 40                 | Art. 714 - ALT 40                | 1.2 | 1400                    | 1"1/2 M                     | 6                                      | 17          | 137                                  | 112 | 76   | 24   |      |      |
| Art. 705 - ALM 50                 |                                  | 2   | 1400                    | 2" M                        | 6                                      | 29          | 205                                  | 176 | 140  | 104  | 69   |      |
|                                   | Art. 715 - ALT 50                | 2.5 | 1400                    | 2" M                        | 6                                      | 29          | 205                                  | 176 | 140  | 104  | 69   |      |

Caratteristiche riferite al funzionamento con acqua. Ci riserviamo la facoltà di apportare modifiche senza obbligo di preavviso / Performances referred to operation with water We reserve the right to make modifications without prior notice / Caracteristiques référées au fonctionnement avec eau. Sous réserve de modifications sans avis préalable