




RIV 3150

Raccordo tre pezzi
 maschio portagomma curvo
 sede metallica

Disegni tecnici e tavole




DN	Codice	H	F	PN	KG	P/box
1" x 25	033150000247	86	13	10	0,24	12
1" x 30	033150000250	101	13	10	0,37	8
1"1/2 x 40	033150000332	120	16	10	0,67	4
1"1/4 x 30	033150000290	99	13	10	0,40	8
1"1/4 x 35	033150000292	112	15	10	0,54	5
1"1/4 x 40	033150000295	121	15	10	0,64	4
1/2" x 15	033150000165	60	10	10	0,10	20
1/2" x 18	033150000167	66	10	10	0,14	10
1/2" x 20	033150000168	72	10	10	0,15	10
2" x 50	033150000371	145	16	10	1,13	5
2" x 60	033150000373	160	20	10	1,69	3
2"1/2 x 60	033150000417	157	18	10	1,57	3
3/4" x 20	033150000210	73	11	10	0,16	10
3/4" x 25	033150000213	82	10	10	0,22	15
3/8" x 15	033150000134	60	9	10	0,11	20

Dati tecnici

Art. 3100

Materiali

1 Corpo Ottone CW617N



Attacco	ISO 228/1
Limite	-10°C (in assenza di liquido) + 100°C
Note	La pressione max. di utilizzo (PN) si intende a temperatura ambiente di circa 23°C.