



MADE IN ITALY

SOLLEVATORI IDRAULICI PER FOSSA E SOTTOPONTE

HYDRAULIC TRANSMISSION JACKS
VERINS DE FOSSE HYDRAULIQUES
HYDRAULISCHE GETRIEBEBEHER

12



- Art. SIF 1/73 - 0,25 Ton.
- Art. SIF 1/A/73 - 0,4 Ton.
- Art. SIF 2/A/73 - 0,6 Ton.
- Art. SIF 2/73 - 1 Ton.
- Art. SIF 3/73 - 1,5 Ton.
- Art. SIF 4/73 - 2,5 Ton.
- Art. SIF 5/73 - 6 Ton.
- Art. SIF 6/73 - 10 Ton.

con stelo cromato
 chromium plated rod
 tige chromée
 verchromter kolben



Art. SIF 1/73



Art. SIF 2/A/73



Art. SIF 3/73



Art. SIF 6/73

Art.		SIF 1/73	SIF 1/A/73	SIF 2/A/73	SIF 2/73	SIF 3/73	SIF 4/73	SIF 5/73	SIF 6/73
Portata Load capacity Portée Tragkraft:	Ton.	0,25	0,4	0,6	1	1,5	2,5	6	10
Altezza minima Minimum height Hauteur minimum Mindesthöhe:	mm.	1240	1240	1180	1190	1220	1350	1305	1315
Corsa 1° stelo First rod stroke Course première tige Hub 1. Stufe:	mm.	850	850	780	800	800	870	900	900
Larghezza base Base width Largeur de la base Basisbreite:	mm.	410	410	520	530	540	550	720	720
Lunghezza base Base length Longueur de la base Basislänge:	mm.	585	585	520	530	540	550	720	720
Ø stelo Ø rod Ø tige Ø Hub:	mm.	22	24	30	35	45	50	60	60

Art. SIF 4/73 - SIF 5/73 - SIF 6/73:
 Forniti con doppio gruppo pompante.
 Supplied with double pumping group.

Fournis avec double groupe pompant.
 Mit 2 Hubgeschwindigkeiten.

Art. SIF 5/73 - SIF 6/73:

Vengono forniti con ruote rientranti con carico ≥ 300 Kg.

Livrés avec roues escamotables avec poids ≥ 300 Kg.

They are supplied with retractile wheels with charge ≥ 300 Kg.

Mit einfedernden Rädern mit Last ≥ 300 Kg.