

PARTE RIF.	TAGLIA TUBO			ROD		OD		MAX WP		BURST PRESSURE		MIN.BEND RADIUS		PESO		RACCORDOMF3000	MONTAGGIOMF2000
	DN	trattino	pollice	mm	pollice	mm	pollice	bar	psi	bar	psi	mm	pollice	g / m	lb / ft		
H09067005	5	-3	3/16"	-	-	11.0	0.43	35	500	140	2030	35	1.38	93	6	-	MF + M00820-03
H09067006	6	-4	1/4"	-	-	12.6	0.50	30	430	120	1740	45	1.77	117	7	-	MF + M00820-04
H09067008	8	-5	5/16"	-	-	14.1	0.56	30	430	120	1740	65	2.56	135	10	-	MF + M00820-05
H09067010	10	-6	3/8"	-	-	15.8	0.62	30	430	120	1740	75	2.95	165	11	-	MF + M00820-06
H09067012	12	-8	1/2"	-	-	19.4	0.76	30	430	120	1740	90	3.54	215	15	-	MF + M00820-08
H09067016	16	-10	5/8"	-	-	23.0	0.91	30	430	120	1740	115	4.53	285	19	-	MF + M00820-10
H09067019	19	-12	3/4"	-	-	26.0	1.02	30	430	120	1740	140	5.51	325	22	-	MF + M00820-12
H09067025	25	-16	1"	-	-	32.0	1.26	30	430	120	1740	150	5.91	430	29	-	MF + M00820-16