

SMAW WELDING

SARFLEX



■ Cavo unipolare extraliscivibile in rame con rivestimento in PVC (HD7R/MK). Temperatura max di esercizio: 70°C sul conduttore. Marcatura: SARFLEX.

■ Extra-flexible unipolar cable in copper with PVC (HD7R/MK) sheath. Maximum operating temperature: 70°C on conductor. Marking: SARFLEX.



CODE	Ø	X 100%	X 60%	X 35%	Ω	↓ MAX
CAV000008	10 mm²	90 A	110 A	175 A	1,910 Ohm/km	70°
CAV000006	10 mm²	90 A	110 A	175 A	1,910 Ohm/km	70°
CAV000007	16 mm²	125 A	160 A	235 A	1,210 Ohm/km	70°
CAV000009	16 mm²	125 A	160 A	235 A	1,210 Ohm/km	70°
CAV000010	16 mm²	125 A	160 A	235 A	1,210 Ohm/km	70°
CAV000011	25 mm²	170 A	210 A	320 A	0,780 Ohm/km	70°
CAV000013	25 mm²	170 A	210 A	320 A	0,780 Ohm/km	70°
CAV000014	25 mm²	170 A	210 A	320 A	0,780 Ohm/km	70°
CAV000018	35 mm²	215 A	260 A	400 A	0,554 Ohm/km	70°
CAV000020	35 mm²	215 A	260 A	400 A	0,554 Ohm/km	70°
CAV000021	35 mm²	215 A	260 A	400 A	0,554 Ohm/km	70°
CAV000025	50 mm²	275 A	346 A	510 A	0,386 Ohm/km	70°
CAV000027	50 mm²	275 A	346 A	510 A	0,386 Ohm/km	70°
CAV000028	50 mm²	275 A	346 A	510 A	0,386 Ohm/km	70°
CAV000035	70 mm²	345 A	425 A	640 A	0,272 Ohm/km	70°
CAV000037	70 mm²	345 A	425 A	640 A	0,272 Ohm/km	70°
CAV000041	95 mm²	420 A	520 A	780 A	0,205 Ohm/km	70°
CAV000043	120 mm²	480 A	620 A	900 A	0,161 Ohm/km	70°