



DF/7



Supporto girevole in lamiera stampata e zincata con attacco a codolo filettato.
Sistema rotante su doppia corona di sfere.

Swivel pressed steel, zinc plated housing, with threaded stem fitting.
Double ball race.

mm	Type	DaN	mm	mm	mm	mm	mm	mm	mmxmm	mm
40L	DF/7	20	54	12,5	25	M10	29	24x5,2	-	
40	DF/7	25	62,5	18,5	25	M10	34	24x6-7	-	
50	DF/7	35	67,5	18,5	25	M10	34	24x6-7	77	
63	DF/7	40	80	18,5	25	M10	34	28x7-8	77	
80	DF/7	50	98	18,5	25	M10	34	28x7-8	77	
100	DF/7	50	118	20	25	M10	34	28x7-8	-	

DF/2/7



DE/7

∅ =
13/15/17/19/
21/24/26
■ =
13/15/17/22



Supporto girevole in lamiera stampata e zincata con attacco ad espansione.
Sistema rotante a doppia corona di sfere.

Swivel pressed steel, zinc plated housing, with rubber expander fitting.
Double ball race.

mm	Type	DaN	mm	mm	mm	mm	mm	mm	mmxmm	mm
40	DE/7	25	62,5	18,5	25	*	34	24x6-7	-	
50	DE/7	35	67,5	20	25	*	34	24x6-7	77	
63	DE/7	40	80	20	25	*	34	28x7-8	77	
80	DE/7	50	98	20	25	*	34	28x7-8	77	

DE/2/7



DA/7

∅ =
12/14/16/18/
20/23



Supporto girevole in lamiera stampata e zincata con attacco a bussola alettata in plastica nera.
Sistema rotante su doppia corona di sfere.

Swivel pressed steel, zinc plated housing, with black plastic finned socket fitting.
Double ball race.

mm	Type	DaN	mm	mm	mm	mm	mm	mm	mmxmm	mm
40	DA/7	25	62,5	18,5	25	*	34	24x6-7	-	
50	DA/7	35	67,5	18,5	25	*	34	24x6-7	77	
63	DA/7	40	80	18,5	25	*	34	28x7-8	77	
80	DA/7	50	98	18,5	25	*	34	28x7-8	77	

DA/2/7



VARIANTI - OPTIONS

--	--	--